

**DRAFT DESIGN CRITERIA FOR ROOFTOP SOLAR INSTALLATIONS
IN THE ENTRANCE CORRIDOR OVERLAY DISTRICT
Revision #2**

General Goals

1. To the greatest extent possible, choose locations, mounting options, and design features that will minimize visibility of the facility from the EC street.
2. Panels and related items must not interfere with elements that contribute to the architectural composition, style or character of the building.

Solar Facilities Mounted on Pitched Roofs Must Have

1. Panels mounted in a manner that establishes an orderly and coordinated appearance and that avoids disjointed arrangements and stair stepping.
2. Panels located parallel to and set back a minimum of 12" from the ridge, eaves and edges of the roof.
3. Panels mounted parallel to the roof plane.
4. Panels of consistent size and color.
5. Fixed, non-moveable panels.
6. Panels mounted such that there is no more than 812" from surface of roof to the underside top of the panel.
7. Conduit, hardware, and related equipment located interior to the building or on walls not visible from the EC. If interior or invisible locations are not available, use matte finishes and colors consistent with the color of the surface to which the equipment is attached.
8. Panels, frames and attached hardware in a consistent color, coordinated with the building whenever possible.
9. Mounting systems that do not extend beyond the panels or the roof.

NOTE: If solar panels are installed on roofs that are not visible from the Entrance Corridor street and in a manner that renders the installation not visible from the Entrance Corridor street, ARB approval of the design is not required. Documentation confirming lack of visibility will be required for staff review.

Solar Facilities Mounted on Flat Roofs Must Have

1. Panels arranged in an organized pattern that establishes a coordinated and orderly appearance consistent with the architecture.
2. A mounting design that is unobtrusive or is an element that complements the building.
3. Conduit, hardware, and related equipment located interior to the building or on walls not visible from the EC. If interior or invisible locations are not available, use matte finishes and colors consistent with the color of the surface to which the equipment is attached.

NOTE: If parapets or other parts of the building eliminate visibility of the solar installation as viewed from the Entrance Corridor street, ARB approval of the design is not required.

Documentation confirming lack of visibility will be required for staff review.

Note: Solar parking canopies are not included in this category of Countywide Certificate of Appropriateness.